



## PXC05 Series

Single and Dual Output 5W  
DC-DC Converters

- Industry Standard 24 Pin Dip Package
- Five Sided Shielding
- Wide Range 4:1 Input
- 3.3, 5, 12, 15 Volt Outputs
- Pin & Surface Mount Models

### Key Market Segments & Applications

Telecom  
Datacom  
Factory Automation & Process Control

### PXC05 Features and Benefits

#### Features

- UL, C-UL, TUV, CE approvals
- Wide range input
- Five sided shielding

#### Benefits

- Easier system approvals
- Less parts to inventory
- Reduced radiated noise

#### Specifications

ITEMS	PXC05
Max Output Power	5W
Voltage Accuracy	+/-2%
Voltage Adjustment	None
Minimum Load (1)	10%
Line Regulation	+/-0.2%
Load Regulation (25% to 100%)	Single Output: +/-0.5%, Dual Output: +/-1%
Cross Regulation (25% to 100%)	Dual +/-5%
Ripple and Noise	50mVp-p (20MHz bandwidth)
Start up time	600ms
Temperature Coefficient	<+/-0.02%/°C
Operating Temperature	See derating curves
Maximum Case Temperature	+100°C
Storage Temperature	-55°C to +105°C
Thermal Shock	MIL-STD-810D
Relative Humidity (non condensing)	5 to 95%
Transient Response	200µs recovery (25% step load change)
Overvoltage Protection	None
Overcurrent Protection	Typically at 170%, self recovery
Input Surge Voltage (Max for 100ms)	12V input: 36V, 24V input: 50V, 48V input: 100V
Reflected input ripple (peak to peak)(2)	20mA
Isolation Voltage	1600VDC min.
Isolation Resistance	10 <sup>9</sup> Ω min.
Isolation Capacitance (max)	300pF
Typical Switching Frequency (Fixed)	300kHz
MTBF (BELLCORE TR-NWT-000332)	3,165,000 hours
Vibration	10 - 55Hz, 2G, 30 minutes each X, Y, Z axis
Conducted and Radiated Emissions	EN55022 Level A
Immunity	EN61000-4-2, -3, -4, -5, -6 Pref Criteria 2
Safety Agency Approval	IEC60950-1, UL/CSA60950-1, EN60950-1, CE Mark
Size mm (L x W x H)	32 x 21 x 11
Weight (g)	DIP 16 SMD 18
Warranty (yrs)	3


**Notes:** (1) To meet regulation & noise specifications. Operation at zero load will not damage the device  
(2) 12µH source impedance in series with + input (3) SMD package: Add suffix "/SMD" to model number.

Model Selector							
Model	Output Voltage (V)	Output Current (mA)	Output Power (W)	Input Voltage (V)	Nominal Input Current (mA)	Efficiency (%)	Max Load Capacity (uF)
<b>Single Outputs</b>							
PXC05-24WS3P3	3.3	1000	3.3	9 - 36VDC	191	76	2200
PXC05-48WS3P3	3.3	1000	3.3	18 - 75VDC	100	73	2200
PXC05-24WS05	5	1000	5	9 - 36VDC	285	77	1000
PXC05-48WS05	5	1000	5	18 - 75VDC	145	76	1000
PXC05-24WS12	12	470	5.64	9 - 36VDC	309	80	220
PXC05-48WS12	12	470	5.64	18 - 75VDC	155	80	220
PXC05-24WS15	15	400	6	9 - 36VDC	329	80	150
PXC05-48WS15	15	400	6	18 - 75VDC	167	79	150
<b>Dual Outputs</b>							
PXC05-24WD05	+/-5	+/-500	5	9 - 36VDC	282	78	+/-680
PXC05-48WD05	+/-5	+/-500	5	18 - 75VDC	145	76	+/-680
PXC05-24WD12	+/-12	+/-230	5.52	9 - 36VDC	295	82	+/-100
PXC05-48WD12	+/-12	+/-230	5.52	18 - 75VDC	151	80	+/-100
PXC05-24WD15	+/-15	+/-190	5.7	9 - 36VDC	313	80	+/-68
PXC05-48WD15	+/-15	+/-190	5.7	18 - 75VDC	159	79	+/-68


DIP Pin Connection			
Pin #	Single	Function	Dual
2	- Input		- Input
3	- Input		- Input
9	NC		Common
10	no pin		no pin
11	NC		- Output
23	+ Input		+ Input
22	+ Input		+ Input
16	- Output		Common
15	no pin		no pin
14	+ Output		+ Output

SMD Pin Connection			
Pin #	Single	Function	Dual
2	- Input		- Input
3	- Input		- Input
9	NC		Common
10	NC		NC
11	NC		- Output
23	+ Input		+ Input
22	+ Input		+ Input
16	- Output		Common
15	NC		NC
14	+ Output		+ Output
Others	NC		NC

**Derating Curve PXC05 Series**



**Outline Drawing PXC05 Series**





**TDK-Lambda France SAS**

3 Avenue du Canada  
 Parc Technopolis  
 Bâtiment Sigma  
 91940 les Ulis  
 France  
 Tel: +33 1 60 12 71 65  
 Fax: +33 1 60 12 71 66  
[france@fr.tdk-lambda.com](mailto:france@fr.tdk-lambda.com)  
[www.fr.tdk-lambda.com](http://www.fr.tdk-lambda.com)



**Italy Sales Office**

Via Giacomo Matteotti 62  
 20092 Cinisello Balsamo (MI)  
 Italy  
 Tel: +39 02 61 29 38 63  
 Fax: +39 02 61 29 09 00  
[info.italia@it.tdk-lambda.com](mailto:info.italia@it.tdk-lambda.com)  
[www.it.tdk-lambda.com](http://www.it.tdk-lambda.com)



**Netherlands**

[info@nl.tdk-lambda.com](mailto:info@nl.tdk-lambda.com)  
[www.nl.tdk-lambda.com](http://www.nl.tdk-lambda.com)



**TDK-Lambda Germany GmbH**

Karl-Bold-Strasse 40  
 77855 Achern  
 Germany  
 Tel: +49 7841 666 0  
 Fax: +49 7841 5000  
[info.germany@de.tdk-lambda.com](mailto:info.germany@de.tdk-lambda.com)  
[www.de.tdk-lambda.com](http://www.de.tdk-lambda.com)



**Austria Sales Office**

Aredstrasse 22  
 2544 Leobersdorf  
 Austria  
 Tel: +43 2256 655 84  
 Fax: +43 2256 645 12  
[info@at.tdk-lambda.com](mailto:info@at.tdk-lambda.com)  
[www.de.tdk-lambda.com](http://www.de.tdk-lambda.com)



**Switzerland Sales Office**

Eichtalstrasse 55  
 8634 Hombrechtikon  
 Switzerland  
 Tel: +41 44 850 53 53  
 Fax: +41 44 850 53 50  
[info@ch.tdk-lambda.com](mailto:info@ch.tdk-lambda.com)  
[www.de.tdk-lambda.com](http://www.de.tdk-lambda.com)



**Nordic Sales Office**

Haderslevvej 36B  
 DK-6000 Kolding  
 Denmark  
 Tel: +45 8853 8086  
[info@dk.tdk-lambda.com](mailto:info@dk.tdk-lambda.com)



**TDK-Lambda UK Ltd.**

Kingsley Avenue  
 Ilfracombe  
 Devon EX34 8ES  
 United Kingdom  
 Tel: +44 (0) 12 71 85 66 66  
 Fax: +44 (0) 12 71 86 48 94  
[powersolutions@uk.tdk-lambda.com](mailto:powersolutions@uk.tdk-lambda.com)  
[www.uk.tdk-lambda.com](http://www.uk.tdk-lambda.com)



**TDK-Lambda Ltd.**

1 Alexander Yanai  
 Segula  
 Petah-Tikva  
 Israel  
 Tel: +9 723 902 4333  
 Fax: +9 723 902 4777  
[info@tdk-lambda.co.il](mailto:info@tdk-lambda.co.il)  
[www.tdk-lambda.co.il](http://www.tdk-lambda.co.il)



**C.I.S.**

**Commercial Support:**  
 Tel: +7 (495) 665 2627  
**Technical Support:**  
 Tel: +7 (812) 658 0463  
[info@tdk-lambda.ru](mailto:info@tdk-lambda.ru)  
[www.tdk-lambda.ru](http://www.tdk-lambda.ru)

**Local Distribution**

